



A = 2.00 * No. of Spaces

B = A + 2.00

* Available in 8 through 50 circuits

Material:
* Contact: Brass

Ordering Code

CH72 22 2 V 1 00
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Plating Code:

Code	Contact Area	Solder Area	Under Plating
A	Gold flash	100u" Tin	50u" Nickel
1		100u" Tin	30u" Nickel
2	Gold flash		50u" Nickel
3	15u" Gold		50u" Nickel
4	30u" Gold		50u" Nickel

④ V= Straight

⚠ ⑤ Insulation: 1= Nylon 6T UL 94V-0, Color Black

⑥ Pin Length Option code:

Option Code	Dimension	
	C	D
00	4.00(.157)	2.80(.110)

Recommended P.C. Board Layout

RoHS Compliant

	Sandy	12/14/05'	ECN05417/ECR05119-0		DATE	UNIT: mm / inch	TITLE: 2.00MM(.079") DUAL ROW BOARD MOUNT PIN HEADER	 瀚荃股份有限公司 CviLux Corporation	
	Sandy	9/08/04'	ECN04340		DRAWN BY: Sandy	12/15/05'	TOLERANCE UNLESS OTHERWISE SPECIFIED		MATERIAL:
	Casey	5/28/04'	ECN04208		ENGINEER: Eisley	12/15/05'	.X ± 0.30 / .012 X" ± 1"		FINISH:
	SUN	4/09/04'	ECN04144		CHECKED BY: David	12/19/05'	.XX ± 0.20 / .010 X" ±		DRAWING NO. CH7201SF
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	12/19/05'	.XXX ± 0.10 / .004 XX" ±	SCALE 3 / 1	SHEET 1 OF 1	