



A = 2.00 X No. of Spaces  
 B = A + 2.00

⚠\* Available in 6 through 50 circuits

Material:  
 \* Contact: Brass

Ordering Code

CH72 22 2 H 1 00  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ⚠ ③ Plating Code:

Code	Contact Area	Solder Area	Under Plating
A	Gold flash	100u" Tin	50u" Nickel
C	30u" Gold	100u" Tin	50u" Nickel
1		100u" Tin	30u" Nickel
2	Gold flash		50u" Nickel
3	15u" Gold		50u" Nickel
4	30u" Gold		50u" Nickel

- ④ H= Right angle
- ⑤ Insulation: 1= Nylon 6T UL 94V-0, Color Black
- ⑥ Pin Length Option code:

Option Code	Dimension	
	C	D
00	4.00(.157)	2.80(.110)

Recommended P.C. Board Layout

RoHS Compliant

⑥	Karen	5/19-10'	ECN10162		DATE	UNIT: mm / inch	TITLE: 2.00MM(.079") RIGHT ANGLE DUAL ROW BOARD MOUNT PIN HEADER	 瀚荃股份有限公司 CviLux Corporation	
⑤	Karen	9/10/08'	ECN8441		DRAWN BY: Karen	5/19-10'	TOLERANCE UNLESS OTHERWISE SPECIFIED		MATERIAL:
④	Sandy	12/14/05'	ECN05417/ECR05119-0		ENGINEER: Clark	5/19-10'	.X ± 0.30 / .012 X* ± 1"		FINISH:
③	Sandy	9/08/04'	ECN04340		CHECKED BY: David	5/19-10'	.XX ± 0.20 / .010 .X* ±		
SYM	NAME	DATE	REVISIONS		APPROVED BY: David	5/19-10'	.XXX ± 0.10 / .004 .XX* ±		
DRAWING NO.		CH7202SH	PART NO.		CH72***H100		SCALE		3 / 1