



Wire Range	Insulation Diameter	Reel Q'ty
AWG #26~#30	1.35 (.053) MAX.	15,000 PCS.

Ordering Code :

CD02 T01 A B P S
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Terminal version: T01= For AWG #26~#30
- ③ Plating code:
 - 2= Gold flash plated over $1.27\mu\text{m}$ (50μ "") Nickel
 - A= Selective Gold flash plated over $1.27\mu\text{m}$ (50μ "") Nickel
 - B= Selective $0.38\mu\text{m}$ (15μ "") Gold plated over $1.27\mu\text{m}$ (50μ "") Nickel
 - C= Selective $0.76\mu\text{m}$ (30μ "") Gold plated over $1.27\mu\text{m}$ (50μ "") Nickel
- ④ Material: B= Brass
- ⑤ Plating method: P= Post plating
- ⑥ Type: S= Receptacle terminal

RoHS Compliant

SYM	NAME	DATE	REVISIONS	APPROVED BY:	DATE	UNIT: mm / inch	TITLE:	CviLux Corporation			
④	Sun	7/20-09'	ECR9077-1/ECN09354			UNIT: mm / inch	CRIMP TERMINAL	瀚荃股份有限公司 CviLux Corporation			
③	Karen	4/15-09'	ECR09041-1/ECN09194	DRAWN BY:	Karen	7/20-09'					
②	Sun	12/03-07'	ECR07151-3/ECN07466	ENGINEER:	Eisley	7/23-09'	MATERIAL:	DRAWING NO. CD0205SH PART NO. CD02T01*BPS			
①	Sandy	11/5/04'	ECN04435	CHECKED BY:	Eisley	7/23-09'	FINISH:				
				APPROVED BY:	Alex	7/23-09'		SCALE	5 / 1	SHEET	1 OF 1

CIVILUX CORP
 2009.07.28
 ISSUED