


SEC.:A-A



SEC.:B-B

Port No.	Wire Range	Insulation Diameter	Reel Q'ty
CD52T02*PPS	AWG #22~#24	1.60 (.063) MAX.	10,000 PCS.

Ordering Code:

△ CD52 T 02 * P P S
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② T= Terminal
- ③ Crimping style:
02= for AWG # 22~ AWG #24
- ④ Plating option:
2= Gold flash plated over Nickel
A= Selective Gold flash plated over 1.27μm(50μ") Nickel
B= Selective 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel
C= Selective 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
- △ ⑤ Material: P= Phosphor Bronze
- ⑥ Plating method: P= Post plating
- ⑦ Crimping terminal: S= Female

RoHS Compliant

△ 4						UNIT: mm / inch	TITLE: CRIMP TERMINAL	瀚荃股份有限公司 CviLux Corporation			
△ 3	Sandy	3/18-09'	ECN09134	2009.03.24	DRAWN BY: Sandy	3/18-09'	MATERIAL:				DRAWING NO.
△ 2	Sun	12/03-07'	ECR07151-3/ECN07466	ISSUED	ENGINEER: Eisley	3/18-09'	TOLERANCE UNLESS OTHERWISE SPECIFIED	FINISH:	SCALE	5 / 1	SHEET 1 OF 1
△ 1	Jessie	9/25/03'	ECN03317		CHECKED BY: David	3/18-09'	.X ± 0.20/.008 X* ± 1'				
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	3/18-09'	.XX ± 0.10/.004 X* ±				
							.XXX ± 0.05/.002 .XX* ±				