

Materials:


- * Insulator: Glass filled polyester UL 94V-0
- * Contacts: Phosphor Bronze
- * Shell: Steel, Tin plated as standard


Ordering Code:

CD67 25 S A 1 00
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Contacts:
- ③ Contact type: S= Receptacle(Female)
- ④ Plating option:
A= Selective Gold flash plated over 1.27 μ m(50 μ "") Nickel
B= Selective 0.38 μ m(15 μ "") Gold plated over 1.27 μ m(50 μ "") Nickel
C= Selective 0.76 μ m(30 μ "") Gold plated over 1.27 μ m(50 μ "") Nickel
- ⑤ Color: 1= Black
- ⑥ Other Option: 00= Standard

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: D-SUB TOP ENTRY BOARD MOUNT FEMALE CONNECTOR	 瀚荃股份有限公司 CviLux Corporation				
③					DRAWN BY: Rita	11/27 03'	TOLERANCE UNLESS OTHERWISE SPECIFIED				MATERIAL:	DRAWING NO.
②					ENGINEER: David	11/30 03'	.X \pm 0.30 / .012 X' \pm 1"	FINISH:	SCALE	2 / 1	SHEET	1 OF 1
①					CHECKED BY: David	11/30 03'	.XX \pm 0.20 / .010 .X' \pm					
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	11/30 03'	.XXX \pm 0.10 / .004 .XX' \pm					


 2001.11.30
 ISSUED