

Materials:


- \* Insulator: Glass filled polyester UL 94V-0
- \* Contacts: Copper alloy
- \* Shell: Steel, Tin plated as standard

Ordering Code:

CD67 09 P A 1 00  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Contacts:
- ③ Contact type: P= Plug(Male)
- ④ Plating option:  
 2= Gold flash plated over 1.27 $\mu$ m(50 $\mu$ ) Nickel  
 A= Selective Gold flash plated over 1.27 $\mu$ m(50 $\mu$ ) Nickel  
 B= Selective 0.38 $\mu$ m(15 $\mu$ ) Gold plated over 1.27 $\mu$ m(50 $\mu$ ) Nickel  
 C= Selective 0.76 $\mu$ m(30 $\mu$ ) Gold plated over 1.27 $\mu$ m(50 $\mu$ ) Nickel
- ⑤ Color: 1= Black
- ⑥ Other Option: 00= Standard

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: D-SUB TOP ENTRY BOARD MOUNT MALE CONNECTOR	 瀚荃股份有限公司 CviLux Corporation	
③				DRAWN BY: Sun	12/1 03'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:		
②				ENGINEER: Eisley	12/2 03'	.X $\pm$ 0.30 / .012 X' $\pm$ 1"	FINISH:		
①	SUN	12/01/03'	ECN03434	CHECKED BY: David	12/2 03'	.XX $\pm$ 0.20 / .010 .X' $\pm$			
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	12/3 03'	.XXX $\pm$ 0.10 / .004 .XX' $\pm$	DRAWING NO. CD6702SD	PART NO. CD6709P*100	
								SCALE 2 / 1	SHEET 1 OF 1

CVILUX.CORP  
 2003.12.03  
 ISSUED