



Material:
 * Insulator: Glass filled polyester UL 94V-0
 * Contact: Brass

Ordering Code:

CD91 25 P * * 00
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Contacts: 9,15,25,37
- ③ Contact type: P= Plug
- ④ Plating option:
 2= Gold flash plated over 1.27μm(50μ") Nickel
 A= Selective Gold flash plated over 1.27μm(50μ") Nickel
 B= Selective 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel
 C= Selective 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
- ⑤ Insulator Color: 1= Black
 7= Blue
- ⑥ Other Option:
 00= All plastic with 3.5mm holes with S/R(Standard)

Circuits	Dimension				
	A	B	C	D	E
9	25.00(.984)	30.8(1.213)	16.92(.666)	22.4(.882)	12.08(.476)
15	33.30(1.311)	39.2(1.543)	25.25(.994)	30.8(1.213)	19.70(.776)
25	47.10(1.854)	53.1(2.091)	38.96(1.534)	44.5(1.752)	32.40(1.276)
37	63.50(2.500)	69.4(2.732)	55.42(2.182)	61.4(2.417)	47.72(1.879)

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: INSULATION DISPLACEMENT D-SUB MALE CONNECTOR	瀚荃股份有限公司 CviLux Corporation
③					DRAWN BY: Sun	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②					ENGINEER: Eisley	.X ± 0.30/.012 X: ± 1'	FINISH:	DRAWING NO. CD9101SD
①	SUN	4/12/04'	ECN04153/ECR04036-0		CHECKED BY: David	.XX ± 0.20/.008 X: ±		SCALE 2 / 1
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	.XXX ± 0.10/.004 XX: ±		SHEET 1 OF 1

CIVILUX.CORP
 2004.04.15
 ISSUED